

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 2429
SRM Name: Flue Gas Desulfurization Gypsum
Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is intended for use in the evaluation of chemical methods of analysis for mercury and other contaminants in gypsum materials. A unit of SRM 2429 consists of 200 g of gypsum derived from flue gas desulfurization (FGD) technologies, further processed to pass a 74 um (200 mesh) sieve, homogenized, and packaged in an amber glass bottle.

Company Information

National Institute of Standards and Technology
 Standard Reference Materials Program
 100 Bureau Drive, Stop 2300
 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200
 FAX: 301-948-3730
 E-mail: SRMMSDS@nist.gov
 Website: <http://www.nist.gov/srm>

Emergency Telephone ChemTrec:
 1-800-424-9300 (North America)
 +1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Note: This particulate material contains respirable quartz. The health and physical hazard information provided in this SDS contains the effects associated with the inhalation of quartz particulates.

Classification

Physical Hazard: Not classified.
Health Hazard: Carcinogen Category 1
 STOT, Repeated Exposure Category 1

Label Elements

Symbol



Signal Word

DANGER

Hazard Statement(s):

H350 May cause lung cancer.
 H372 Causes damage to lungs through prolonged or repeated inhalation.

Precautionary Statement(s):

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust.
 P264 Wash hands thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P280 Wear protective gloves, protective clothing, and eye protection.
 P308 + P313 If exposed or concerned: Get medical attention.
 P405 Store locked up.
 P501 Dispose of contents and container according to local regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients(s) with Unknown Acute Toxicity: Not applicable.

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Gypsum

Other Designations: Agricultural gypsum

Components are listed in compliance with OSHA's 29 CFR 1910.1200; for the actual values see the NIST Certificate of Analysis.

Hazardous Component(s)	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
Calcium sulfate dehydrate	13397-24-5	603-783-2	>93
Quartz	14808-60-7	238-878-4	<0.75

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: Wash skin with soap and water for at least 15 minutes. Thoroughly clean and dry contaminated clothing before reuse.

Eye Contact: Flush eyes with water for at least 15 minutes. If necessary, seek medical attention.

Ingestion: If adverse effects occur after ingestion, seek medical treatment.

Most Important Symptoms/Effects, Acute and Delayed: May cause irritation, lung damage, silicosis, and cancer.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek medical attention if needed.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Negligible fire hazard. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media:

Suitable: Use extinguishing agents appropriate for surrounding fire.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: None listed.

Special Protective Equipment and Precautions for Fire-Fighters: Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1

Fire = 0

Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection".

Methods and Materials for Containment and Clean up: Collect spilled material in appropriate container for disposal. Keep out of water supplies and sewers. Keep unnecessary people away, isolate hazard area and deny entry.

7. HANDLING AND STORAGE

Safe Handling Precautions: Minimize dust generation. See Section 8, "Exposure Controls and Personal Protection".

Storage: Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances (See Section 10, "Stability and Reactivity").

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:

Calcium sulfate dehydrate:

OSHA (PEL): 15 mg/m³ (TWA, total particulates not otherwise regulated)
5 mg/m³ (TWA, respirable particulates not otherwise regulated)

Quartz:

ACGIH (TLV): 0.025 mg/m³ (TWA) [respirable fraction]
OSHA (PEL): (30)/(%SiO₂ + 2) mg/m³ (TWA) [total dust]
(250)/(%SiO₂ + 5) mppcf (TWA) [respirable fraction]
(10)/(%SiO₂ + 2) mg/m³ (TWA) [respirable fraction]
NIOSH (REL): 0.05 mg/m³ (TWA) [respirable dust]
50 mg/m³ (IDLH) [respirable dust]

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles with a face shield. An eyewash station should be readily available near areas of use.

Skin and Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Descriptive Properties:

Appearance (physical state, color, etc.):	white to off-white powder
Molecular Formula:	not applicable
Molar Mass (g/mol):	not applicable
Odor:	low to odorless
Odor threshold:	not available
pH:	6 to 8
Evaporation rate:	not applicable
Melting point/freezing point (°C):	not applicable
Relative Density (water = 1):	2.96
Vapor Pressure (mmHg):	not applicable
Vapor Density (air = 1):	not applicable
Viscosity (cP):	not applicable
Solubility(ies):	soluble in water at 0.15 g/100 g to 0.4 g/100 g
Partition coefficient (n-octanol/water):	not available
Particle Size:	<74 um

Thermal Stability Properties:

Autoignition Temperature (°C):	not applicable
Thermal Decomposition (°C):	1450 °C (2642 °F)
Initial boiling point and boiling range (°C):	not applicable
Explosive Limits, LEL (Volume %):	not applicable
Explosive Limits, UEL (Volume %):	not applicable
Flash Point (°C):	not applicable
Flammability (solid, gas):	not applicable

10. STABILITY AND REACTIVITY

Reactivity: Stable at normal temperatures and pressure.

Stability: Stable Unstable

Possible Hazardous Reactions: None listed.

Conditions to Avoid: Avoid generating dust.

Incompatible Materials: Bases, halogens, acids, metal salts, metal, oxidizing materials, combustible materials.

Fire/Explosion Information: See Section 5, "Fire Fighting Measures".

Hazardous Decomposition: Thermal decomposition will produce calcium oxides, carbon dioxide, carbon monoxide and miscellaneous decomposition products.

Hazardous Polymerization: Will Occur Will Not Occur

11. TOXICOLOGICAL INFORMATION

Route of Exposure: Inhalation Skin Ingestion

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: May cause irritation, lung damage, silicosis, and cancer.

Potential Health Effects (Acute, Chronic and Delayed):

Inhalation: Acute exposure to fine particles containing respirable quartz may result irritation; chronic exposure may result in irritation, chest pain, weight loss, difficulty breathing, digestive disorders, bluish skin color, lung damage, cancer, and death.

Skin Contact: May cause irritation due to mechanical abrasion.

Eye Contact: May cause irritation due to mechanical abrasion.

Ingestion: No data available.

Numerical Measures of Toxicity:

Acute Toxicity: Not classified; no data available.

Skin Corrosion/Irritation: Not classified; no data available.

Serious Eye Damage/Irritation: Not classified; no data available.

Respiratory Sensitization: Not classified; no data available.

Skin Sensitization: Not classified; no data available.

Germ Cell Mutagenicity: Not classified; no data available.

Carcinogenicity: Category 1

Listed as a Carcinogen/Potential Carcinogen Yes No

Silica dust, crystalline, in the form of quartz is listed by IARC, Group 1, carcinogenic to humans. Silica, Crystalline is listed by NTP as a known human carcinogen (respirable size). Quartz is not listed by OSHA as a designated carcinogen.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (STOT), Single Exposure: Not classified; no data available.

Specific Target Organ Toxicity (STOT), Repeated Exposure: Category 1; Cumulative exposure may result in reduced lung capacity and silicosis.

Aspiration Hazard: Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity Data:

Calcium sulfate dehydrate: Fish: fathead minnow (*Pimephales promelas*) LC50: >1970 mg/L

Quartz: No data available.

Persistence and Degradability: Calcium sulfate dissolves in water forming calcium and sulfate ions.

Bioaccumulative Potential: None expected.

Mobility in Soil: No data available.

Other Adverse effects: None expected.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of waste in accordance with all applicable federal, state, and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: Not regulated by DOT or IATA.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Not regulated.

SARA Title III Section 302 (40 CFR 355.30): Not regulated.

SARA Title III Section 304 (40 CFR 355.40): Not regulated.

SARA Title III Section 313 (40 CFR 372.65): Not regulated.

OSHA Process Safety (29 CFR 1910.119): Not regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH:	Yes.
CHRONIC HEALTH:	Yes.
FIRE:	No.
REACTIVE:	No.
PRESSURE:	No.

State Regulations:

California Proposition 65: WARNING! This product contains a chemical (quartz of respirable size) known to the state of California to cause cancer.

U.S. TSCA Inventory: Quartz is listed. Calcium sulfate dehydrate is not listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations:

WHMIS Information: Not provided for this material.

16. OTHER INFORMATION

Issue Date: 09 September 2015

Sources: USG, Vendor SDS, *USG Synthetic Gypsum*, 01 June 2015
ChemAdvisor, Inc., SDS *Quartz*, 20 March 2015.

CDC; NIOSH; *NIOSH Pocket Guide to Chemical Hazards*; Department of Health and Human Services (DHHS), Centers for Disease Control and Prevention (CDC), National Institute for Safety and Health; *Particulates not otherwise regulated*, 13 February 2015; available at <http://www.cdc.gov/niosh/npg/npgd0480.html> (accessed Sep 2015).

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists	NIST	National Institute of Standards and Technology
ALI	Annual Limit on Intake	NRC	Nuclear Regulatory Commission
CAS	Chemical Abstracts Service	NTP	National Toxicology Program
CEN	European Committee for Standardization	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	PEL	Permissible Exposure Limit
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
CPSU	Coal Mine Dust Personal Sample Unit	REL	Recommended Exposure Limit
DOT	Department of Transportation	RM	Reference Material
EC50	Effective Concentration, 50 %	RQ	Reportable Quantity
EINECS	European Inventory of Existing Commercial Chemical Substances	RTECS	Registry of Toxic Effects of Chemical Substances
EPCRA	Emergency Planning and Community Right-to-Know Act	SARA	Superfund Amendments and Reauthorization Act
IARC	International Agency for Research on Cancer	SCBA	Self-Contained Breathing Apparatus
IATA	International Air Transportation Agency	SRM	Standard Reference Material
IDLH	Immediately Dangerous to Life and Health	STEL	Short Term Exposure Limit
ISO	International Organization for Standardization	STOT	Specific Target Organ Toxicity
LC50	Lethal Concentration, 50 %	TDLo	Toxic Dose Low
LD50	Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
NIOSH	National Institute for Occupational Safety and Health	WHMIS	Workplace Hazardous Materials Information System

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at <http://www.nist.gov/srm>.