



DATE: 01 August 2013

Product Identifier

SRM Number: 1364b

SRM Name: Coating Thickness Standard (Nonmagnetic Coating on Steel)

Under the U.S. Department of Labor, Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1200, this Standard Reference Material (SRM) is NOT classified as a physical hazard or a health hazard, a simple asphyxiant, combustible dust, pyrophoric gas, or hazard not otherwise classified. There are no hazard pictograms, hazard statements or signal word associated with it. Safety Data Sheet information is not required. This document may be used in conjunction with your hazard communication program.

Exemption: 1910.1200 (c). This SRM is an Article, as the word is defined by OSHA, where *Article* means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of 1910.1200), and does not pose a physical hazard or health risk to employees.

Description: This SRM is designed for calibrating coating thickness gauges that employ magnetic principles. These gauges are used to measure the thickness of nonmagnetic coatings on steel including paint and other organic coatings, as well as nonmagnetic metallic coatings. A unit of SRM 1364b consists of a preconfigured set of five 45 mm × 45 mm coupons: a bare substrate, and four coupons with metallic coatings certified for total coating thickness (nominal coating thicknesses of 800 μm, 1000 μm, 1525 μm, and 1935 μm). Each coupon consists of an AISI 1010 cold-rolled sheet-steel substrate with the coated coupons possessing an additional uniform coating of copper that is overlaid with a thin protective layer of chromium. This SRM is one in a series of SRMs prepared to cover a coating thickness range from 6 μm to 1935 μm.

Disposal: SRM 1364b components should be disposed of in accordance with local, state, and federal regulations.

Transport Information: This material is not regulated by the U.S. Department of Transportation (DOT) and/or International Air Transportation Association (IATA).

Disclaimer: This document was prepared carefully, using current references. Users of this SRM should ensure that this document and the corresponding Certificate of Analysis in their possession are current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at <http://www.nist.gov/srm>.