

**SAFETY DATA SHEET**

**1. SUBSTANCE AND SOURCE IDENTIFICATION**

**Product Identifier**

**RM Number:** 8027  
**RM Name:** Silicon Nanoparticles (Nominal Diameter 2 nm)  
**Other Means of Identification:** Not applicable.

**Recommended Use of This Material and Restrictions of Use**

This Reference Material (RM) is intended primarily to evaluate and qualify methodology and/or instrument performance related to the physical/dimensional characterization of nanoscale particles. A unit of RM 8027 consists of five hermetically sealed pre-scored glass ampoules each containing nominally 1 mL of cyclohexane-stabilized silicon (Si) nanocrystals suspended in toluene. The suspension contains particles (monomers) and a small percentage of clusters of primary particles.

**Company Information**

National Institute of Standards and Technology  
 Standard Reference Materials Program  
 100 Bureau Drive, Stop 2300  
 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200  
 FAX: 301-948-3730  
 E-mail: SRMMSDS@nist.gov  
 Website: <http://www.nist.gov/srm>

Emergency Telephone ChemTrec:  
 1-800-424-9300 (North America)  
 +1-703-527-3887 (International)

**2. HAZARDS IDENTIFICATION**

**Note:** The concentration of silicon nanoparticles in this suspension is below the reportable limit for SDS information as required by OSHA 29 CFR 1910.1200 (see Report of Investigation for concentration value). This material should be handled as recommended by the National Institute for Occupational Safety and Health (NIOSH). According to NIOSH, occupational health risks associated with manufacturing and using nanomaterials are not fully understood. Minimal information is currently available on dominant exposure routes, potential exposure levels, and material toxicity of nanomaterials.

**Classification**

<b>Physical Hazard:</b>	Flammable liquid	Category 2
<b>Health Hazard:</b>	Acute Toxicity, Inhalation	Category 4
	Skin Corrosion/Irritation	Category 2
	Serious Eye damage/Eye irritation	Category 2B
	Reproductive Toxicity	Category 2
	STOT, Single Exposure	Category 3
	STOT, Repeated Exposure	Category 2
	Aspiration Hazard	Category 1

**Label Elements**

**Symbol**



**Signal Word**

DANGER

**Hazard Statement(s)**

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315+H320	Causes skin and eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs (eyes, skin, respiratory system, central nervous system, liver, kidneys) through prolong or repeated exposure (inhalation, ingestion, skin contact).

**Precautionary Statement(s)**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use regular dry chemical, carbon dioxide, water, or regular foam media for extinction.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents according to local/regional/national/international regulations.

**Hazards Not Otherwise Classified:** Not applicable.

**Ingredients(s) with Unknown Acute Toxicity:** Not applicable.

---

### 3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

---

**Substance:** Cyclohexane-stabilized Si nanocrystals suspended in toluene.

**Other Designations:**

Toluene (methylbenzene; toluol; 1-methylbenzene; methylbenzol; phenylmethane; methyl benzene)

Components are listed in compliance with OSHA's 29 CFR 1910.1200; for the actual values see the Report of Investigation.

Hazardous Component(s)	CAS Number	EC Number (EINECS)	Nominal Concentration (%)
Toluene	108-88-3	203-625-9	<99

---

## 4. FIRST AID MEASURES

---

### Description of First Aid Measures:

**Inhalation:** If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

**Skin Contact:** Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. Thoroughly clean and dry contaminated clothing before reuse. Destroy contaminated shoes.

**Eye Contact:** Immediately flush eyes, including under the eyelids with copious amounts of water for at least 15 minutes. Seek immediate medical attention.

**Ingestion:** Aspiration hazard! *Do not* induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get immediate medical attention. Give artificial respiration if not breathing.

**Most Important Symptoms/Effects, Acute and Delayed:** Respiratory tract, skin, and eye irritation; aspiration hazard, nervous system depression, and nerve damage.

**Indication of any immediate medical attention and special treatment needed, if necessary:** If any of the above symptoms are present, seek immediate medical attention.

---

## 5. FIRE FIGHTING MEASURES

---

**Fire and Explosion Hazards:** Severe fire hazard. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Vapor/air mixtures are explosive. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion. See Section 9, "Physical and Chemical Properties" for flammability properties.

### Extinguishing Media:

Suitable: Regular dry chemical, carbon dioxide, water, regular foam.

Unsuitable: None listed.

**Specific Hazards Arising from the Chemical:** Thermal decomposition products: oxides of carbon, hydrocarbons.

**Special Protective Equipment and Precautions for Fire-Fighters:** Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

**NFPA Ratings** (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 2

Fire = 3

Reactivity = 0

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal Precautions, Protective Equipment and Emergency Procedures:** Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Immediately contact emergency personnel. Isolate hazard area, and deny entry. Reduce vapors with water spray. Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection".

**Methods and Materials for Containment and Clean up:** Do not touch spilled material. Notify safety personnel of spills. Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Avoid and remove sources of ignition. Keep out of water supplies and sewers.

---

## 7. HANDLING AND STORAGE

---

**Safe Handling Precautions:** Open glass ampoules carefully to prevent contamination and injury. See Section 8, "Exposure Controls and Personal Protection".

**Storage:** Until required for use, the RM should be stored at room temperature in its original ampoule and package, and protected from intense direct light or ultraviolet radiation. Refrigeration and heating above 40 °C is discouraged. Ampoules are best stored long term in a horizontal position. Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances (oxidizing materials, halogens, combustible materials, acids, metal salts).

---

---

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

---

### Exposure Limits:

Toluene:

NIOSH (REL): 375 mg/m<sup>3</sup>; 100 ppm (TWA)  
560 mg/m<sup>3</sup>; 150 ppm (STEL)  
1885 mg/m<sup>3</sup>; 500 ppm (IDLH)  
ACGIH (TLV): 75 mg/m<sup>3</sup>; 20 ppm (TWA)  
OSHA (PEL): 750 mg/m<sup>3</sup>; 200 ppm (TWA)  
1130 mg/m<sup>3</sup>; 300 ppm (Ceiling)

**Engineering Controls:** Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

**Personal Protection:** In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

**Respiratory Protection:** If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

**Eye/Face Protection:** Wear splash resistant safety goggles with a face shield. An eyewash station should be readily available near areas of use.

**Skin and Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**NOTE:** The physical and chemical data provided are for the pure hazardous components. No physical or chemical data are available for this solution.

	<b>Toluene</b> (>99 % of this SRM)
<b>Descriptive Properties:</b>	
<b>Appearance (physical state, color, etc.):</b>	clear, colorless liquid
<b>Molecular Formula:</b>	C <sub>7</sub> H <sub>8</sub>
<b>Molar Mass (g/mol):</b>	92.14
<b>Odor:</b>	distinct odor
<b>Odor threshold:</b>	10 ppm to 15 ppm
<b>pH:</b>	not available
<b>Evaporation rate (butyl acetate = 1):</b>	2.24
<b>Melting point/freezing point (°C):</b>	-95 (-139 °F)
<b>Sublimation Point (°C):</b>	not applicable
<b>Decomposition (°C):</b>	not applicable
<b>Relative Density as specific gravity (water = 1):</b>	0.8669
<b>Vapor Pressure:</b>	22 mmHg at 20 °C
<b>Vapor Density (air = 1):</b>	3.14
<b>Viscosity (cP):</b>	0.560 cP at 25 °C
<b>Solubility(ies):</b>	water solubility: 0.05 % at 20 °C; soluble in alcohol, ether, benzene, chloroform, ligroin, acetic acid, carbon disulfide, acetone
<b>Partition coefficient (n-octanol/water):</b>	log Kow = 2.73
<b>Particle Size (if relevant)</b>	not applicable

	<b>Toluene</b>
<b>Thermal Stability Properties:</b>	(>99 % of this SRM)
Autoignition Temperature (°C):	480 (896 °F)
Thermal Decomposition (°C):	not applicable
Initial boiling point and boiling range (°C):	111 (232 °F)
Explosive Limits, LEL (Volume %):	1.2
Explosive Limits, UEL (Volume %):	7.1
Flash Point (°C):	4 (39.2 °F) CC
Flammability (solid, gas):	not applicable

## 10. STABILITY AND REACTIVITY

**Reactivity:** Stable at normal temperatures and pressure.

**Stability:**      Stable      Unstable

**Possible Hazardous Reactions:** No data available.

**Conditions to Avoid:** Avoid heat, flames, sparks and other sources of ignition. Ampoules may rupture or explode if exposed to heat. Keep out of water supplies and sewers.

**Incompatible Materials:** Oxidizing materials, halogens, combustible materials, acids, metal salts.

**Fire/Explosion Information:** See Section 5, "Fire Fighting Measures".

**Hazardous Decomposition:** Thermal decomposition will produce oxides of carbon, hydrocarbons.

**Hazardous Polymerization:**  Will Occur      Will Not Occur

## 11. TOXICOLOGICAL INFORMATION

**Route of Exposure:**      Inhalation      Skin      Ingestion

**Symptoms Related to the Physical, Chemical and Toxicological Characteristics:** Respiratory tract, skin, and eye irritation; aspiration hazard, nervous system depression, and nerve damage.

**Potential Health Effects (Acute, Chronic and Delayed):**

**Inhalation:** Exposure to 100 ppm may cause irritation. Levels of 200 ppm to 600 ppm for up to 8 h caused fatigue, weakness, confusion, headache, nausea, impaired coordination and reaction time, paresthesias of the skin, euphoria, dizziness, and dilated pupils. Exposure to 800 ppm caused rapid irritation, nasal mucous secretion, metallic taste, drowsiness, and impaired balance. After effects including nervousness, muscular fatigue, and insomnia lasted for several days.

**Skin Contact:** Contact with liquid may cause irritation and dermatitis due to defatting.

**Eye Contact:** Irritation with redness and pain and conjunctivitis.

**Ingestion:** Aspiration hazard; ingestion of toluene can cause lung damage and death.

**Numerical Measures of Toxicity:**

**Acute Toxicity:** Category 4, inhalation.

Toluene: Rat, Oral LD50: 636 mg/kg  
Rat, Dermal LD50: 8390 mg/kg  
Rat, Inhalation LC50: 12.5 mg/L (4 h)

**Skin Corrosion/Irritation:** Category 2

Toluene: Rabbit, Dermal: 435 mg (mild); 500 mg (moderate); 20 mg (moderate, 24 h)

**Serious Eye damage/Eye irritation:** Category 2B

Toluene: Rabbit, Eye: 870 µg (mild); 100 mg/30 s rinse (mild); 2 mg (severe, 24 h)

**Respiratory Sensitization:** No data available.

**Skin Sensitization:** No data available.

**Germ Cell Mutagenicity:** Not classified.

Toluene: Human, Inhalation: 252 µg/L (19 years)

**Carcinogenicity:** Not classified.

**Listed as a Carcinogen/Potential Carcinogen** \_\_\_\_\_ Yes \_\_\_\_\_ X No  
Toluene is not listed by NTP or OSHA as a carcinogen; IARC lists toluene as Group 3, *not classifiable*.

**Reproductive Toxicity:** Category 2B

Toluene: Endpoints listed for reproductive effects on embryo or fetus  
Rat, Oral, TDLo: 7280 mg/kg (pregnant 6 d to 19 d),  
fetotoxicity (except death, e.g., stunted fetus)  
Mouse, Oral, TDLo: 9 g/kg (pregnant 6 d to 15 d), fetal death

**Specific Target Organ Toxicity, Single Exposure:** Category 3 (narcotic effects)

See health effects listed in "Potential Health Effects (Acute, Chronic and Delayed)".

**Specific Target Organ Toxicity, Repeated Exposure:** Category 2

Prolonged or repeated exposure may cause mucous membrane irritation, vomiting, insomnia, nosebleeds, chest pains, euphoria, headache, vertigo, nausea, anorexia, momentary loss of memory, loss of coordination and impairment of reaction time, tinnitus, impaired speech, vision, and/or hearing, alcohol intolerance, and petechiae and abnormal bleeding. Volunteers exposed to 200 ppm for 6 hours/day for 2 days showed a significant increase in heart rate. Cardiac sensitization may occur and may result in cardiac arrest due to ventricular fibrillation. Repeated inhalation to the point of euphoria has caused irreversible encephalopathy with cerebellar ataxia, rhythmic limb movements, disequilibrium, bizarre behavior, emotional lability, optic atrophy, and diffuse cerebral atrophy.

**Aspiration Hazard:** Category 1

Toluene is reported as an aspiration hazard.

---

## 12. ECOLOGICAL INFORMATION

---

### Ecotoxicity Data:

Toluene:  
Fish Toxicity: Rainbow trout (*Oncorhynchus mykiss*) LC50 (flow-through): 5.9 mg/L to 7.8 mg/L (96 h)  
Invertebrate: Freshwater water flea (*Daphnia magna*) EC50 (static): 5.5 mg/L to 9.8 mg/L (48 h)

**Persistence and Degradability:** No data available.

**Bioaccumulative Potential:** No data available.

**Mobility in Soil:** No data available

**Other Adverse effects:** No data available.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Waste Disposal:** Dispose of waste in accordance with all applicable federal, state, and local regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262, Hazardous Waste Number: U220 (Toluene).

---

## 14. TRANSPORTATION INFORMATION

---

**U.S. DOT and IATA:** UN1294, Toluene, Hazard Class 3, Packing Group II, Excepted Quantities E2.

---

## 15. REGULATORY INFORMATION

---

### U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): 5000 lbs (2270 kg) final RQ for toluene.  
SARA Title III Section 302 (40 CFR 355.30): Not regulated.  
SARA Title III Section 304 (40 CFR 355.40): Not regulated.  
SARA Title III Section 313 (40 CFR 372.65): 1.0 % de minimis concentration for toluene.  
OSHA Process Safety (29 CFR 1910.119): Not regulated.  
SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH:	Yes.
CHRONIC HEALTH:	Yes.
FIRE:	Yes.
REACTIVE:	No.
PRESSURE:	No.

**State Regulations:**

California Proposition 65: WARNING! This product contains a chemical (toluene) known to the state of California to cause reproductive/developmental effects.

**U.S. TSCA Inventory:** Toluene is listed.

**TSCA 12(b), Export Notification:** Not listed.

**Canadian Regulations:**

WHMIS Information: Not provided for this material.

**16. OTHER INFORMATION**

**Issue Date:** 22 November 2013

**Sources:** ChemAdvisor, Inc., MSDS *Toluene*, 18 October 2013.

Hazardous Substances Data Bank, National Library of Medicine, *Toluene CAS 108-88-3*, Full Record, available at <http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB> (accessed Nov 2013).

NIOSH Pocket Guide to Chemical Hazards, *Toluene CAS 108-88-3*, (4 April 2011), available at <http://www.cdc.gov/niosh/npg/npgd0619.html> (accessed Nov 2013); also see *RTECS #: XS5250000*, (May 2009); at <http://www.cdc.gov/niosh-rtecs/XS501BD0.html> (accessed Nov 2013)

NIOSH Publications, *Approaches to Safe Nanotechnology: Managing the Health and Safety Concerns Associated with Engineered Nanomaterials*; available at <http://www.cdc.gov/niosh/docs/2009-125/> (accessed Nov 2013)

NIOSH Publications, *General Safe Practices for Working with Engineered Nanomaterials in Research Laboratories*; available at <http://www.cdc.gov/niosh/docs/2012-147/> (accessed Nov 2013)

**Key of Acronyms:**

ACGIH	American Conference of Governmental Industrial Hygienists	NRC	Nuclear Regulatory Commission
ALI	Annual Limit on Intake	NTP	National Toxicology Program
CAS	Chemical Abstracts Service	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	PEL	Permissible Exposure Limit
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EC50	Effective Concentration, 50 %	RM	Reference Material
EINECS	European Inventory of Existing Commercial Chemical Substances	RQ	Reportable Quantity
EPCRA	Emergency Planning and Community Right-to-Know Act	RTECS	Registry of Toxic Effects of Chemical Substances
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transportation Agency	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
LC50	Lethal Concentration, 50 %	STEL	Short Term Exposure Limit
LD50	Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
NIOSH	National Institute for Occupational Safety and Health	UEL	Upper Explosive Limit
NIST	National Institute of Standards and Technology	WHMIS	Workplace Hazardous Materials Information System
n.o.s.	Not Otherwise Specified		

**Disclaimer:** Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Report of Investigation.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail [srmmsds@nist.gov](mailto:srmmsds@nist.gov); or via the Internet at <http://www.nist.gov/srm>.